

# GigaSwitch V5 7 Port 54VDC Series

## Contact

Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## LANactive 7 Port Managed Full Gigabit Ethernet FTTO Switch

- 3 Uplink Ports (2x SFP and 1x RJ45)
- Power over Ethernet (PoE+), up to 150W
- Efficient Energy Management
- Memory Card Slot
- Input voltage range 46 ... 57V DC

## Description

Nexans LANactive GigaSwitch V5 series is designed for the installation in Fibre to the Office (FTTO) networks. The latest generation of FTTO switches is equipped with a state-of-the-art network processor and provides enhanced performance, security and redundancy functionality.

### 7 Port Version

The GigaSwitch version with seven ports is part of the latest V5 series. This special variant with three uplink ports allows a redundant connection of the GigaSwitch via fibre optic. The RJ45 uplink can be used for connecting an additional Wireless LAN Access Point. All uplinks support Link Aggregation for providing redundancy and double bandwidth up to 2Gbps.

### Snap-In Installation

The very compact design of the GigaSwitch allows a tool-less snap-in installation into the standard 45 mm cable duct systems or floor boxes without special mounting accessories.

### Power over Ethernet

Up to 5x connected Ethernet devices can be supplied with Power over Ethernet. According to the latest IEEE 802.3at (PoE+) standard, up to 30 watts per port are available for each connected device, with total budget of 150 watts.

### Memory Card

The optional memory card automatically saves the complete current configuration and firmware of the device. In case of failure, this feature allows an easy exchange of the hardware without additional configuration. In addition, each memory card can be delivered with its own MAC address that is adopted by the switch.

### Switch Management and Zero-Touch Configuration

Nexans LANactive Manager allows a simple and secure configuration of all device parameter of the GigaSwitch series. With the LANactive Manager a larger number of GigaSwitches can be managed and monitored at the same time. In combination with Nexans Zero-Touch Configuration, the LANactive Manager allows automatic distribution of configurations and firmware updates. A pre-configuration of the switches is not necessary.



Made in Germany

**LANactive**  
Switch to the future

## Standards

IEEE 802.3  
IEEE 802.3u  
IEEE 802.3ab  
IEEE 802.3af  
IEEE 802.3at  
IEEE 802.3z  
IEEE 802.3x  
IEEE 802.1AB  
IEEE 802.1D  
IEEE 802.1Q  
IEEE 802.1X  
IEEE 802.1AX  
IEEE 802.3ad



Real-Time OS  
Yes



PoE/PoE+  
Yes



Compact design  
45x90mm



Noiseless  
Yes



Fast Installation  
Yes



Redundancy  
Yes



Operating Temperature  
0 ... 45 °C



Electromagnetic Shielding  
Yes

**Nexans**

# GigaSwitch V5 7 Port 54VDC Series

## Contact

Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## Hardware Features

Ordering Information	GigaSwitch V5 TP(PSE+) SFP-2VI 54VDC		GigaSwitch V5 TP SFP-2VI 54VDC	
Article Number	88303910	88313910	88303920	88313920
Switching Type	Store-and-Forward, self-learning			
Non-blocking Switching Capacity	20Gbps			
Packet Forwarding Rate	2x 1.488Mpps per port			
Max. Frame Size	9,600Bytes	10,240Bytes	9,600Bytes	10,240Bytes
Packet Buffer	512kBytes	256kBytes	512kBytes	256kBytes
MAC-Address Table	8k	16k	8k	16k
<b>Interfaces</b>				
User Ports (RJ45)	4x 1000Base-T			
Uplink Ports (SFP)*	2x 1000Mbps			
Uplink Ports (RJ45)	1x 1000Base-T			
RJ45 Ports	Auto-Negotiation, MDI/MDI-X Auto-Cross Over and Auto-Polarity			
Digital Diagnostics Monitoring (SFP)	Yes			
Twisted Pair Cable Diagnostic	Yes			
Rotatable Head Module	Yes			
<b>Power over Ethernet</b>				
Number of PoE User Ports	4x PSE(PoE+) acc. to IEEE802.3at			
Number of PoE Uplink Ports	1x PSE(PoE+) acc. to IEEE802.3at			-
PoE Mode	30W per Port, Mode A, Pin 1-2/3-6			
Max. PoE power budget	150W		120W	
<b>General</b>				
Dimensions [W x H x D]	90mm x 45mm x 69mm			
Installation Depth	35mm			
Material	zinc diecasting / stainless steel			
Colour	Pure White, like RAL 9010			
Ambient Temperature	Operation: 0 ... 45°C, Storage: -20 ... 85°C			
Relative Humidity	20 ... 90% (non-condensing)			
Weight	290g			
MTBF	> 750,000h			
<b>Power Supply</b>				
Input Voltage	46 ... 57V DC (typ. 54V DC)			
Power Consumption	4.4W typ., 6.2W max.			
Heat Output	22Btu(IT)/h			
Connector	3-pin connector (up to 2.5mm <sup>2</sup> ) / (+) (-) (FPE)			
<b>CE - Conformity</b>				
Electro Magnetic Capability Directive	2014/30/EU			
Low Voltage Directive	-			
RoHS 2	2011/65/EU			
Engineering Standards	EN 62368-1, EN 55032, EN 55024, EN 50581			

\* 88303910 and 88303920 are supporting 100Mbps as well

## Switch and Software Features

### Switching Parameters

VLANs	IEEE802.1q with up to 256 Groups
Quality of Service Layer 2	IEEE802.1p Class of Service (4 Queues per Port)
Quality of Service Layer 3	RFC2474/3168 DSCP (4 Queues per Port)
Bandwidth Limitation	Bitrate
Energy Efficient Ethernet	IEEE802.3az
Flow Control	IEEE802.3x
Fabric Attach	Basic Fabric Attach Client Support

### Management

LEDs	On-Board High-Performance Management
Zero-Touch Configuration	Management, Port Status and Activity, Memory Card Via LANactive Manager Controller
IP-Address	IPv4, IPv6
DHCP-Client	DHCP, DHCPv6
DHCP Relay Agent	Yes
File Transfer	TFTP, SCP
Console Port	V.24 with Nexans Console Cable
Web-Interface	HTTP, HTTPS
Command Line Interface	SSH, Telnet, V.24
Scripting	Yes
SNMP	SNMPv1, v2c, v3
Syslog	Yes
Discovery Protocols	LLDP (IEEE802.1AB), LLDP-MED (ANSI/TIA-1057), CDP
Time Synchronisation	SNTP
Port Statistics	Detailed per Port

### Redundancy

Redundancy Protocols	STP, RSTP, MSTP, MRP
Link Aggregation	LACP

### Security

Password Protection	Two Access Levels (R/W or R/O)
Authentication via Radius and TACACS+	CLI and LANactive Manager
ACL for Management Interface	Up to 16 Access Control Lists
Portsecurity via MAC-Address	Up to 3 predefined MAC-Addresses
Portsecurity via Radius	IEEE802.1x with MAC Bypass
DHCP Snooping	Yes
Loop and Broadcast Limiter	Yes
Firmware Update	Dual Firmware Image
Configuration-/Reset Button	Yes / Yes
Memory Card	micro SD-Card with own MAC-Address (optionally)

# GigaSwitch V5 7 Port 54VDC Series

Contact  
Nexans LAN Systems  
Tel.: +49 (0) 2166 27 2220  
sales.ans@nexans.com

## Dimensions

